

- ▶ Digital Pin-Point Leak Location
- ▶ Equipped with External Braid
- ▶ Embedded Microprocessor
- ▶ Water and Base Liquids Detection
- ▶ Designed for Suspended Pipe Solution

Description

The TTK digital sense cable FG-ECB detects and pinpoints the location of water and base liquid leaks at any point along its length. It is designed to operate with the FG-SYS, FG-NET, or FG-BBOX digital units, enabling intelligent response in the event of a leak. The FG-ECB sense cable is supplied with an external polyethylene-based braided jacket and is specifically designed for pipe applications. (It can be secured in place using a cable tie, if required.)

Key Advantages

- Available in standard and pre-connected lengths of 3, 7 and 15 m. They can be interconnected to provide an expandable network of leak detection.
- Performing the same function as the FG-EC digital sense cable, the FG-ECB sense cables contain an embedded microprocessor. They intelligently monitor the cable status and provide continuous real-time communication to the TTK digital units.
- Each cable has a high-visibility LED to provide quick green/red identification of the cable status:
 - Green LED: normal status, no alarm raised;
 - Red LED: leak detection on the cable;
 - LED off: cable break on this or any upstream cable.
- Ingenious design: external polyethylene based braided jacket and 4 PEHD conducted helical construction - connected on an extruded central core. It is insensitive to dust and metal particle contamination, preventing false alarms.
- A set of TTK bus 8723 jumper cables and connection accessories gives continuity to each circuit.
- Detects and pinpoints the location of a water or base leak to the nearest metre along the length of the cable.
- Detects and localizes cablebreak on the cable.
- The FG-ECB sense cable is a non-absorbent design that can be reused after leaks. Cable drying is easy.
- An external polyethylene based braided jacket keeps water around the cable thus assures an efficient detection.
- Easy installation with pre-finished male and female connectors. FG-ECB is to install under the suspended pipes, attached to the underside of the pipes. No drip tray is needed.
- Flexible design: supports both linear and sector modes (via FG-DTC box).

Technical Data

Compatibility	Digital units: FG-SYS; FG-NET; FG-BBOX Diversion box: FG-DTC
Reusability	Reusable, as long as the cable hasn't been damaged by prolonged immersion in liquid
Drying Time for Cable After Leak	30 seconds
Sense Cable Nominal Diameter	7 mm (± 0.5mm) without braid, 10 mm (±0.5mm) with braid
Central Core Material	LSF (Low Smoke and Fume)
Minimum Bend Radius	20 mm
Braid Colour	White
Operating Temperature	-15°C to 55°C
Connector Ingress Protection	IP 67


Product Diagram

Embedded Microprocessor in Female Connector:




- Green LED: Normal Status
- Red LED: Leak Detected on the Cable

FG-ECB Sense Cable



FG-ECB Sense Cable Cutting View (Without Braid)

2 communication wires and 2 detection and location wires



Non-contractual images

Identification Codes

FG-ECB3	Braided Addressable Water Sense Cable in 3 m with Connectors
FG-ECB7	Braided Addressable Water Sense Cable in 7 m with Connectors
FG-ECB15	Braided Addressable Water Sense Cable in 15 m with Connectors
Accessories:	
FG-CLC	Leader Cable, on TTK Bus 8723
FG-TMC	Digital End Plug for Water & Acids Cables
FG-NC'N'	TTK Bus 8723 Neutral Cable 'N' (1, 10, 15 m) with Connectors
CF-EC100	100 Hold-down Clips with Adhesive for Water & Acids Cables
ES-EC	40 Tags for Water & Acids Cables

Certification



All TTK sense cables are designed as a part of the leak detection system thus included in the approval certification for TTK monitoring panels. FG-NET and FG-SYS systems meet the requirements of all European Standards in EN 50081 and EN 50082 EMC. FG-NET and FG-SYS systems are UL Listed.

This brochure has been carefully prepared to ensure technical accuracy but is only intended for promotional use. TTK cannot guarantee that the information contained herein contains no errors or omissions, and hence does not accept responsibility related to the use of its equipment. TTK maintain its obligations set forth in the Standard Terms and Conditions of Sale and will not, under any circumstances, assume liability for any incidental damages, indirect or consequential, arising from the sale, resale, use or misuse of this project. The purchaser(s) accept their responsibility as the sole judge(s) of the adaptability of the product for the intended use. FG-NET, FG-SYS and TOPSurveillance are trademarks of TTK S.A.S. © TTK 2025

- **TTK UK Ltd.** / 3 Luke Street / London EC2A 4PX / United Kingdom / T : +44 207 729 6002 / F : +44 207 729 6003 / www.ttkuk.com / sales@ttkuk.com
- **TTK Pte Ltd.** / #09-05, Shenton House, 3 Shenton Way / Singapore 068805 / T: +65.6220.2068 / M: +65.9271.6191 / F: +65-6220.2026 / www.ttk.sg / info@ttk.sg
- **TTK Asia Ltd.** / 2107-2108 Kai Tak Commercial Building / 317 Des Voeux Road Central / Hongkong / T: +852.2858.7128 / F: +852.2858.8428 / www.ttkasia.com / info@ttkasia.com
- **TTK Middle East FZCO** / Building 6EA, Office 510 PO Box 54925 / Dubai Airport Free Zone / UAE / T: +971 4 70 17 553 / M: +971 50 259 66 29 / www.ttkuk.com / cgalniche@ttk.fr
- **TTK Headquarters** / 19, rue du Général Foy / 75008 Paris / France / T : +33.1.56.76.90.10 / F : +33.1.55.90.62.15 / www.ttk.fr / ventes@ttk.fr